



LED Edgelit Display Panels

Front view




Back view




LED Light Box

LED light boxes are lit from two edges in an ultra-slim snap frame that secures your interchangeable graphic while providing the maximum illumination for any environment.

Front view



Back view



LED U-Channel

Typically used in displays, exhibits, branding design solutions and architectural lighting.

LED panels are lit from two edges and held in place with a u-channel frame allowing for more permanent display environments.

Call
800-869-7800
for more
information



Light Boxes - Edgelit

- Light Guide easily configured to fit edgelit and backlit light boxes
- Utilizes snap frame and channel systems for graphic retention



Light Boxes - Backlit

- Low profile from 3/4" for edgelit and 2-11/32" for backlit (or greater if required)
- Does not contain mercury as in fluorescent bulbs

Accent's line of customizable edgelit LED display panels are designed to integrate functionality, a clean, chic appearance and the brightest edgelit panels on the market. Our panels are made with technology that enhances luminance and delivers ultimate uniformity.

- Ultra-Slim appearance
- Snap frame for removeable graphics or snap u-channel frame for more permanent displays
- Aluminum frame construction
- Standard sizes available
- Custom sizes up to a graphic size of 48" x 96"
- Landscape and portrait orientation
- Anodized finish or custom painted to PMS or color scales Matthews paint
- Easy mounting using L or J brackets, Z clips or channel fastener
- Manufactured in the United States
- 12 month warranty
- LED lifecycle of ~50,000 hours
- Minimal maintenance

LED Ultra-Slim Edgelit Panels

SNAP FRAME SPECIFICATIONS EXAMPLE

Depth:

0.75" (19.05mm)

Graphic Dimensions:

Same as Standard Sizes

Outside Dimensions:

Add 0.364" (9.25 mm) to height

Add .0364" (9.25 mm) to width

Visual Dimensions:

Subtract 0.364" (9.25 mm) from height

Subtract 0.364" (9.25 mm) from width

LEDs:

Ultra-bright strips

UL Recognized components

12 volt, constant current

24 volt panel is UL Listed

Average Current Draw:

0.67 amps per linear foot

Power Consumption:

12 watts per linear foot


Panel Weight:

~ 2.14 lbs per square foot

Standard Sizes			
Inches		mm	
H	W	H	W
11	8.5	279.4	215.9
24	36	609.6	914.4
36	48	914.4	1219.2
20	24	508	609.6

1 Inches = 25.4mm

Call
800-869-7800
for more
information




Light Guide Light Sources


- Custom sizes from 2" x 2" up to 48" x 96"
- Brightest available on the market
- Low profile from 3/4"
- Low power consumption
- Easily configured into many applications

Snap Lock Extrusions


Base Rail 2.0




Base Rail 2.5




Base Rail 2.0 with Snap Cover



Base Rail 2.5 with Snap Cover




Snap Cover



U-Channel Extrusions

Base Rail 3.0



3.5 F-Channel

